



LISA 1

LISA 2

LISA 3


**PRODUCT INFORMATION:**

Thermal energy: 48-54 kWh  
 Energy efficiency: 83 %  
 CO%: 0,09 %  
 Nominal heat output: 1,8 kW / 6,1 hours  
 Heat storage capacity:\*\*  
 100% after 5,1 hours  
 50% after 19,3 hours  
 25% after 31,0 hours




\*\* Information provided by Nunnauni


**LAYOUT DRAWINGS:**



LISA 1,  
LISA 1 PL



LISA 2,  
LISA 2 PL



LISA 3,  
LISA 3 PL

**PRODUCT NUMBER:**

Product	Product number	Weight kg	Height mm
LISA 1	606661-1	1560	1785
LISA 2	606661-2	1670	1785
LISA 3	606661-3	1895	1925
LISA 1 PL	606621-1	1530	1785
LISA 2 PL	606621-2	1640	1785
LISA 3 PL	606621-3	1865	1925

**BOTTOM PLINTHS:**

LISA 1 & LISA 1 PL	200527	85	70
LISA 2 & LISA 2 PL	200605	100	70

**CHANGE OPTIONS:**

- \* Extra layer 280 mm for inner stones
- \* Extra layer 280 mm for outer stones

**NEEDED FOR ASSEMBLY:**

- \* Mortar 1 x 25 kg (not included in NunnaUni delivery)

(...), Bottom plinth dimensions  
 PL = Top connection

## PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)					
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Burning heat output [kW]	Flue connection [A/B] Ø	Burning air approx. m³/h
Lisa 1,2 and 3	-	-	33	15	-	230	15	24,3	31,3	180	70
Lisa PL	-	-	33	15	-	230	15	24,3	31,3	150	70

## FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR		
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT
Lisa 1 and 2	x	x	x	150-180	180	180	1640 (2)	420	-	910400
Lisa 3	x	x	x	150-180	180	180	1780	420	-	910400
Lisa PL	-	-	-	150	-	-	-	420	-	910400

## SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250	
	Behind	On the sides
Lisa 1 and 2	-	-
Lisa 3	-	-
Lisa PL	-	-

- 1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.
- 2) When installing with bottom plinth, flue connection (+70mm) will be raised according to thickness of the plinth.

## Take a notice of the countryspecific approvals in section 3

### NOTES!

The flue heat category required by the fireplace is T350.

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

## Country- and region-specific regulations must be adhered to when installing the fireplace

